

**Bare Extruded Natural Rubber Thread
MATERIAL SAFETY DATA SHEET**

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Bare Extruded Natural Rubber (Talc/Silicone Coated)
 Company Name: Rubberflex Sdn Bhd
 21st Floor, UBN Tower, Jalan P Ramlee
 Box No. 48, 50250, Kuala Lumpur, Malaysia
 Telephone No.: 00-603-20720011
 Fax No.: 00-603-20785103
 Product Name: Bare Extruded Natural Rubber
 Chemical Family: Natural Rubber (cis 1,4 polyisoprene)
 Packing: 10-45 kg packing/box
 Emergency Telephone No.: 00-603-20720011

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

All chemicals are non-toxic/non-hazardous

The chemicals lists are:

NATURAL RUBBER cis 1,4, Polyisoprene
 ZDBC Zinc dibutyl dithiocarbamate
 ZMBT Zinc mercaptobenzothiazole
 KOH Potassium hydroxide
 ANTIOXIDANT Butylated reaction product of p-cresol and dicyclopentadiene
 SULPHUR
 ZnO Zinc oxide
 TiO2 Titanium dioxide
 CALCINED CLAY Kaolin clay
 Talc Magnesium silicate
 Silicone Polydimethyl siloxane

SECTION 3: HAZARDS IDENTIFICATION

None known except for those individuals allergic to natural rubber. Please seek medical advice in case of rashes/itch.

SECTION 4: PHYSICAL DATA

Dimensions

	COARSE GAUGE	MEDIUM GAUGE	FINE GAUGE
TALC COATED	20-44	46-65	70-125
DIAMETER	1.27-0.58	0.55-.39	0.36-.20
YIELD(meters/kg)	745-3604	3940-7867	9300-29650
TOLERANCE	+/-5%	+/-5%	+/-5%
SILICONE COATED	20-44	46-65	--
DIAMETER	1.27-0.58	0.55-.39	--
YIELD(meters/kg)	745-3604	3940-7867	--
TOLERANCE	+/-5%	+/-5%	--

Physical Appearance Ribbon forms festooned in a box with either talcum or silicone coating.

SECTION 5: STABILITY AND REACTIVITY

None known

SECTION 6: QUALITY ASSURANCE CONFORMITY

Conformity ISO 9001 2008
 Okoe-Tex Certified (# 097282)

SECTION 7: ECOLOGICAL INFORMATION

Bio-compatibility: The chemical formulation of the thread and surface lubricating materials do not contain any substances normally known to be harmful to the user or to any person with whom the thread contacts.

SECTION 8: DISPOSAL CONSIDERATION

Product is non-hazardous, non toxic but proper disposal into landfill areas should be considered

SECTION 9: TRANSPORTATION INFORMATION

No special requirements.

SECTION 10: REGULATORY INFORMATION

None known

SECTION 11: OTHER INFORMATION

To prolong product life, rubber thread should be stored in a cool dry location, located away from sources of heat and light

Disclaimer:

These information are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. User is advised to evaluate the fitness or suitability of our product for their own use and Rubberflex Sdn Bhd will not be responsible for any damages/claims arising from these data